OSRAM

ORIGINAL - FESTOON

Original spare part





The cost-effective original spare parts for trucks

The ORIGINAL festoon lamps with OSRAM's reliable OEM quality can be used as original spare parts for 24 volt lamps. The typical application areas of the lamps are number plate and side position lights as well as interior lighting and reading lights.

Technical data

| | Product information | General Product Information | Electrica | Electrical Data | | |
|-----------------------|--|--------------------------------|----------------|-----------------|--------------------|--|
| Product description | Application (Category and Product specific) | Global order reference | Power input | Nominal voltage | Nominal wattage | |
| ORIGINAL FESTOON C5W | Auxiliary lamp | 6423 | 7 W | 24.0 V | 5 W | |
| ORIGINAL FESTOON 6421 | Auxiliary lamp | 6421 | 3 W | 24.0 V | 3 W | |
| ORIGINAL FESTOON 6424 | Auxiliary lamp | 6424 | 7 W | 24.0 V | 5 W | |
| ORIGINAL FESTOON 6429 | Auxiliary lamp | 6429 | 10 W | 24.0 V | 10 W | |

| | | | Photometric Data | | Physical Attributes & Dimensions |
|-----------------------|--------------------------|-----------------|--------------------------|-------------------------------|----------------------------------|
| Product description | Power input tolerance | Test voltage | Nominal luminous flux | Luminous flux tolerance | Lamp base |
| ORIGINAL FESTOON C5W | ±10 % | 28.0 V | 45 lm | ±20 % | SV8.5-8 |
| ORIGINAL FESTOON 6421 | ±10 % | 28.0 V | 17 lm | ±20 % | SV8.5-8 |
| ORIGINAL FESTOON 6424 | ±10 % | 28.0 V | 60 lm | ±20 % | SV8.5-8 |
| ORIGINAL FESTOON 6429 | ±10 % | 28.0 V | 105 lm | ±20 % | SV8.5-8 |

| | | | | Lifetime D | Lifetime Data | |
|-----------------------|---------|----------|----------|----------------|----------------|--|
| Product description | Length | Diameter | Diameter | Lifespan B3 | Lifespan Tc | |
| ORIGINAL FESTOON C5W | 36.0 mm | 11.0 mm | 11.0 mm | 1500 hr | 4000 hr | |
| ORIGINAL FESTOON 6421 | 41.0 mm | 11.0 mm | 11.0 mm | 800 hr | 1500 hr | |
| ORIGINAL FESTOON 6424 | 41.0 mm | 11.0 mm | 11.0 mm | 1000 hr | 2000 hr | |
| ORIGINAL FESTOON 6429 | 41.0 mm | 11.0 mm | 11.0 mm | 300 hr | 600 hr | |

| | Capabilities | Certificates & standards | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | |
|-----------------------|--------------|--------------------------------|--|---------------------------------------|
| Product description | Technology | ECE category | Primary article identifier | Candidate list substance 1 |
| ORIGINAL FESTOON C5W | AUX | C5W | 4050300831435 4008321007711 4050300925981 | No declarable substances contained |
| ORIGINAL FESTOON 6421 | AUX | - | 4008321007896 4008321090768 | No declarable substances contained |
| ORIGINAL FESTOON 6424 | AUX | - | 4050300891712 4008321007742 | No declarable substances contained |
| ORIGINAL FESTOON 6429 | AUX | - | 4008321007568 4008321090836 | No declarable substances contained |

| Product description | Declaration no. in SCIP database |
|----------------------|---------------------------------------|
| ORIGINAL FESTOON C5W | No declarable substances contained |

_

| Product description | Declaration no. in SCIP database |
|-----------------------|---------------------------------------|
| ORIGINAL FESTOON 6421 | No declarable substances contained |
| ORIGINAL FESTOON 6424 | No declarable substances contained |
| ORIGINAL FESTOON 6429 | No declarable substances contained |

File

User instruction

GPRS_Safety symbols instructions

Download Data

1

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





00





