Product family datasheet



LEDriving BASIC R5W



Product family datasheet

Technical data

	Product information		General Product Information		Electric	Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference		Power input	Nominal voltage	
LEDriving BASIC ≜ R5W	Mainly used for signal/ indicator applications	Off-road ≙ R5W	5107CW	,	0.96 W	12.0 V	
				Photomet	ric Data	Physical Attributes & Dimensions	
Product description	Nominal wattage		Test voltage	Nominal lı flux	uminous	Lamp base	
LEDriving BASIC \doteq R5W	0 W	±20 %	13.5 V	55 lm		BA15s	
				Lifetime D	ata	Capabilities	
Product description	Length	Diameter		Lifespan B3	Lifespan Tc	Technology	
LEDriving BASIC \doteq R5W	29.0 mm	19.0 mm		2000 hr	2000 hr	LED	
	Environmental & Regu	•		(EC) 1907/2	006 (REACh)	
Product description	Primary article identifier	Candidate list substance 1		CAS No. of substance 1		Safe use instruction	
LEDriving BASIC ≙ R5W	4052899463332 4052899414556 4052899463127 4052899414532	Lead		7439-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.	

Product description	Declaration no. in SCIP database
LEDriving BASIC ≙ R5W	12c61241-8e84-
	49d2-aad6-
	61ee9185fc4c
	a74edd59-fe84-466f-
	9e9c-d76036657cbc
	4deab8c0-c089-
	4d6a-90f4-
	3738f5af799e
	e8c7bd92-d6cb-4cf2-
	9e8f-8360bae74918
	eb08c6c5-5573-
	4254-af17-
	5f6a4f492b5f

Product family datasheet

Download Data

	File
7	User instruction GPRS_Safety symbols instructions
7	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

