

# TYREinflate 2110



## Large analogue pressure gauge

Easily monitor pressure from a distance for accurate inflation



## 3 m wind-up power cable

Pack up is easy and kink free with the smooth wind-up power cable



## Large, powerful LED light to illuminate workspace

For inflating in dark conditions, the large LED light is designed to illuminate the work area ahead without the need to reposition the inflator



## Powerful, precise, and easy tyre inflation

Introducing the OSRAM TYREinflate 2110, the combination of simplicity and power for hassle-free tyre inflation. This advanced inflator features a large, easy-to-read analogue pressure gauge, delivering precise pressure readings every time. The wind-up 3m 12V power cable allows for a quick and tidy pack-up, while the integrated valve storage post ensures valve caps stay secure during use.

Designed with convenience in mind, the 60cm inflation hose is neatly stored within the unit, and three versatile valve adaptors are safely housed inside, ready for a variety of inflation tasks. Large, intuitive buttons make operation effortless, and its powerful performance can inflate a 13" tyre in just 4 minutes.<sup>1)2)</sup>



Compact, reliable, and user-friendly, the OSRAM TYREinflate 2110 is the solution for drivers who value precision and efficiency on the road.

Product family datasheet

Technical data

Product description	General Product Information	Physical Attributes & Dimensions		
	Global order reference	Height	Width	Length
TYRE inflate 2110	OTI2110	152.0 mm	105.0 mm	220.0 mm
Product description	Operating Conditions	Additional product data	Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Noise Level (dB)	Display Type	Fuse	Candidate list substance 1
TYRE inflate 2110	85 dB	Analogue	10 A	Lead
Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database	
TYRE inflate 2110	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7fd425a7-0e8b-450d-96ad-7bff2ce486b7	

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	User instruction TYREinflate 2110

Legal advice

- 1)Based on inflating a 13” tyre from flat to 2.4 BAR
- 2)Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.