

# TYREinflate 2120



## Large digital display

Effortlessly monitor pressure in BAR, PSI, or kPa with a clear progress bar



## Auto-stop inflator

Inflation accurately stops once desired pressure has been reached



## Large, powerful LED light to illuminate workspace

For inflating in dark conditions, the large LED light is designed to illuminate the work area ahead without the need to reposition the inflator



## Powerful, precise, and easy tyre inflation

Take tyre inflation to the next level with the OSRAM TYREinflate 2120, combining advanced technology with user-friendly design. Featuring a digital pressure gauge and a convenient progress bar, it ensures accurate readings with minimal effort. The auto-inflation function stops precisely at your desired pressure, while the memory function remembers your last setting for seamless repeat use.

Switch easily between PSI, BAR, or kPa to suit your preference, and enjoy the practicality of a 3 m wind-up 12V power cable and a 60 cm inflation hose, both neatly stored within the inflator. A dedicated valve storage post keeps valve caps secure during use, and three versatile valve adaptors are conveniently housed in the unit for added functionality.



Built for speed and precision, the OSRAM TYREinflate 2120 inflates a 13" tyre in just 3.5 minutes, delivering good performance for drivers who demand efficiency and reliability.<sup>1)2)</sup>

Product family datasheet

Technical data

Product description	General Product Information	Physical Attributes & Dimensions		
	Global order reference	Height	Width	Length
TYRE inflate 2120	OTI2120	152.0 mm	105.0 mm	220.0 mm
Product description	Operating Conditions	Additional product data	Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Noise Level (dB)	Display Type	Fuse	Candidate list substance 1
TYRE inflate 2120	85 dB	Digital	15 A	Lead
Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database	
	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	853942bc-69d6-47a2-a1bd-7b39b9ed2006	

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	User instruction TYREinflate 2120 OTI2120

Legal advice

- 1)Based on inflating a 13” tyre from flat to 2.4 BAR
- 2)Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.