

# TYREinflate 2130



### Rapid digital inflator with quick set pressure and auto-stop

Extra large digital display makes monitoring inflation a breeze, whilst quick set pressure with auto-stop ensures accurate inflation every time



### Designed for convenience

Features a wind-up power cable, onboard storage for the air hose and valve adaptors, and even a convenient post to store valve caps during inflation



### Large, powerful LED light to illuminate workspace

For inflating in dark conditions, the large LED light is designed to illuminate the work area ahead without the need to reposition the inflator



### Powerful, precise tyre inflation

Meet the flagship model in the next-generation range: the OSRAM TYREinflate 2130. Designed for those who demand OSRAM's top performance, this advanced inflator features an extra-large digital pressure gauge with a progress bar for clarity and control. The intuitive quick-set dial allows you to input desired pressures in seconds, while the auto-inflation function ensures precise results every time. A convenient memory function recalls your last-used pressure setting for effortless repeat use.

Equipped with a 3.5 m wind-up 12V power cable, a 70 cm extra-long inflation hose, and a dedicated deflate button, the TYREinflate 2130 offers flexibility and control. A valve storage post and securely housed three valve adaptors add to its versatility, making it suitable for various inflation tasks. With a powerful motor that inflates a 13" tyre in just 2 minutes, the OSRAM TYREinflate 2130 delivers speed, power, and precision. <sup>1)2)</sup>

## Product family datasheet

### Technical data

Product description	General Product Information	Physical Attributes & Dimensions		
	Global order reference	Height	Width	Length
TYRE inflate 2130	OTI2130	152.0 mm	105.0 mm	220.0 mm



Product description	Operating Conditions	Additional product data	Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Noise Level (dB)	Display Type	Fuse	Candidate list substance 1
TYRE inflate 2130	85 dB	Digital	15 A	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
TYRE inflate 2130	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a369e638-9ced-4549-a22b-1b08ffe69e69

## Product family datasheet

---

### Download Data

File	
	User instruction TYREinflate 2130
	User instruction GPRS_Safety symbols instructions

#### Legal advice

1)Based on inflating a 13” tyre from flat to 2.4 BAR

2)Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.