OSRAM

TYREinflate 1000



Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 2 minutes**



Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



LED Light

Easy to operate even in darkness and in low light conditions



Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 1000 is a rapid digital tyre inflator with a backlit digital display for easy, accurate pressure readings. Includes an auto stop feature to get the exact desired pressure needed to accurately inflate your tyres. The auto set on the Tyreinflate 1000 is incredibly easy to set up - just turn the dial to the pressure you require, click to set, then press start. The inflator will automatically stop once the correct pressure has been reached.

A wind-up power cable eliminates messy wires and a 2 minute inflation time* gets you on the road and where you need to be quickly. The power cable is long enough (3.5 m) to reach all tyres around your vehicle.

The large on/off button and the LED directional light make the Tyreinflate 1000 easy to use in darkness and emergencies – keeping you prepared for whatever may happen on the road.

Includes 3-piece adaptor for bicycles, balls and other inflatables.

**based on inflating a 13" tyre from flat to 2.41 BAR

Product family datasheet

Technical data

| | | | 1 | |
|---------------------|--------------------------------|---|---|--|
| | General Product Information | Electrical Data | Physical Attributes & Dimensions | |
| Product description | Global order reference | Nominal voltage | Height | Width |
| TYRE inflate 1000 | OTI1000 | 11.1 V | 219.0 mm | 88.0 mm |
| | | Operating Conditions | Additional product | Capabilities |
| Product description | Length | Noise Level (dB) | Display Type | Fuse |
| TYRE inflate 1000 | 200.0 mm | 90 dB | Digital | 15 A |
| | | egulatory Information ing Art. 33 of EU Regulation | (EC) 1907/2006 (REACh |) |
| Product description | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
| TYRE inflate 1000 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 166a46e8-51b1- 466f-9cfd- 6a1cc6989c16 b0abf529-311b-4f43- 8c8e-139c08188c8b |

Product family datasheet

Download Data

| | File |
|----------|--|
| 7 | User instruction TYREinflate 1000 |
| | Movie application OSRAM TYREinflate 1000 Application Video Short (EN) |
| | Movie application OSRAM TYREinflate 1000 Application Video Short (DE) |
| | Movie application TyreInflate How to Video (RU) |
| | Product movie TyreInflate How to Video (EN) |
| | Product movie TyreInflate How to Video (IT) |
| | Product movie TyreInflate 1000 Product Video (RU) |
| D | Product movie TyreInflate 1000 Product Video (EN) |
| D | Product movie TyreInflate 1000 Product Video (ITA) |
| D | Video OSRAM TYREinflate 1000: Rapid tyre inflator with wind-up cable, large digital display and LED light |
| D | Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily |

Safety advice

Product won't exceed noise levels of more than 90 dB

Legal advice

CE and EAC compliant

- * for precise conditions please refer to: www.osram.com/am-guarantee
- ** based on inflating a 13" tyre from flat to 2.41 BARApplication advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Product family datasheet

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.