


Lightbar FX1000-CB SM GEN 2



Single mount certified
For individual installation



Up to 635 m long beam
Improved far and near field illumination



Combo Beam
Designed for both: far-field and near-field illumination



IP & IK protection classes
Tested and validated in a DIN-certified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



Increased brightness for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX1000-CB SM GEN 2 provides additional, near and far field illumination on dark roads with up to 8.000 Lumen. Even in poor visibility conditions or at dusk, the 40 high-performance LEDs reach a light distance of up to 635 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The driving light impresses with its special reflector design and ensure not only a modern and appealing look but also reduces glare for more visibility on the road. It can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads. Additionally, OSRAM has developed a specially designed mounting kit, compatible with all driving lights of the Functional series FX Gen 2 for individual mounting. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan. The LEDriving Lightbar FX1000-CB SM GEN 2 has been tested and validated with the IP-Protection Classes IP6K8 &

IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Its variability gives the FX series a flexible range of uses. They can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads¹⁾. OSRAM provides a 5-year guarantee²⁾. 1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

	Product information	General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Global order reference	Nominal voltage	Nominal wattage
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM ¹⁾	Driving Light - Additional high beam application	LEDDL114-CB SM	12/24 V	140 W

		Photometric Data	LED module information	Lifetime Data	Capabilities
Product description	Test voltage	Nominal luminous flux	Number of LEDs per module	Lifespan Tc	Technology
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM ¹⁾	13.2 V	8000 lm	40	> 5000 hr	LED ²⁾

	Certificates & standards	Logistical data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Product description	ECE reference number	Commodity code	Candidate list substance 1	CAS No. of substance 1
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM ¹⁾	50 + 50	85122000900	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM ¹⁾	The identification of the Candidate List substance is sufficient to allow safe use of the article.	c2b80793-fe0b-4e19-b939-6a319f84b67b

¹⁾ Beam Pattern: Combo
²⁾ Light-emitting diode application

Product family datasheet

Download Data

File	
	User instruction LEDriving Lightbar FX1000-CB SM
	User instruction GPRS_Safety symbols instructions
	Movie application OSRAM LEDriving driving and working lights FX1000-CB SM (EN)
	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application Working and Driving Lights Amarok Winter
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application LEDriving driving & working lights in application (EN)
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	ref_pim_ams_product360degreeimages LEDriving Lightbar FX1000-CB SM LEDDL114-CB SM

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.