

LEDDriving SLT W5W

LEDDriving interior lamps for trucks



LED replacement lamp with a color temperature of up to 6,000 K

Modern and intense uniform illumination



Replaces all conventional W5W 24 V lamp bases

Easy upgrade to LED technology with plug & play solution



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDDriving SLT W5W replacement lamps offer a modern and intense light with a cool white color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SLT lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Nominal voltage	Nominal wattage
LEDriving PREMIUM SL \triangleq W5W	Mainly used for signal/ indicator/ interior applications	Off-road \triangleq W5W	2845DWP	24.0 V	1 W

Product description	Power input tolerance	Test voltage	Power input	Photometric Data		
				Light color LED	Luminous flux tolerance	Nominal luminous flux
LEDriving PREMIUM SL \triangleq W5W	$\pm 25\%$	28.0 V	0.7 W	Cool white	$\pm 25\%$	65 lm

Product description	Color temperature	Physical Attributes & Dimensions		
		Diameter	Diameter	Lamp base
LEDriving PREMIUM SL \triangleq W5W	6000 K	10.1 mm	10.1 mm	W2.1x9.5d

Product description	Length	Product weight	Lifetime Data		
			Lifespan Tc	Guarantee	Lifespan B3
LEDriving PREMIUM SL \triangleq W5W	25.4 mm	1.70 g	3000 hr	4 years	1500 hr

Product description	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDriving PREMIUM SL \triangleq W5W	LED	4062172401814	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving PREMIUM SL \triangleq W5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ce57cdf7-4612-4bc6-936c-acced2979e56

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)
	Brochures Sales Folder LEDriving replacement lamps (EN)

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

